


PC Board Mountable Pressure Sensor Temperature Compensated 0 – 100mV Output Gage, Absolute, Differential Current/Voltage Excitation

1200 Series

The 1200 series is a temperature compensated, piezoresistive silicon pressure sensor packaged in a dual-in-line configuration.

Integral temperature compensation is provided over a wide temperature range using laser-trimmed resistors. An additional laser-trimmed resistor is included to normalize pressure sensitivity variations by programming the gain of an external differential amplifier.



FEATURES

- Dual-in-Line Package
- 1.0% Interchangeable Span (provided by gain set resistor)
- Solid State Reliability
- Wide Compensated Temperature Range

APPLICATIONS

- Medical Instruments
- Airspeed and Altitude Measurements
- Process Control
- Factory Automation
- Vacuum Measurement
- Handheld Calibrators
- Leak Detection
- Sleep Apnea
- Respirators/Ventilators
- Air Duct Flow



1200 Series

Product Definition

Model	Pressure Ranges	Type (G = Gage A = Absolute D = Differential)	Span	Sup Voltage	ply Current	Compensated Temperature	Unique Feature
<u>1210 Sub psi</u>	0 - 5, 10" in H ₂ O	G, D	40mV		1.5mA	0°C to 60°C	Barbed port option Current excitation
<u>1210 1psi</u>	0 - 1psi	G, D	100mV		1.5mA	0°C to 50°C	Current excitation
<u>1210</u> Standard	0 - 2, 5, 15, 30, 50, 100psi	G, A, D	100mV		1.5mA	0°C to 50°C	Current excitation
<u>1220 1psi</u>	0 - 1psi	G, D	50mV	1.235Vref		0°C to 50°C	Voltage excitation
<u>1220</u> Standard	0 - 2, 5, 15, 30, 50, 100psi	G, A, D	50mV	1.235Vref		0°C to 50°C	Voltage excitation
<u>1230</u> <u>UltraStable™</u>	0 - 15, 30, 50, 100psi	G, A, D	100mV		1.5mA	-20°C to +85°C	Current excitation UltraStable™
<u>1240</u> <u>UltraStable</u> ™	0 - 15, 30, 50, 100psi	G, A, D	50mV	1.235Vref		-20°C to +85°C	Voltage excitation UltraStable™

NORTH AMERICA

Measurement Specialties 45738 Northport Loop West Fremont, CA 94538 Tel: 1-800-767-1888 Fax: 1-510-498-1578 Sales: pfg.cs.amer@meas-spec.com

EUROPE

Measurement Specialties (Europe), Ltd. 26 Rue des Dames 78340 Les Clayes-sous-Bois, France Tel: +33 (0) 130 79 33 00 Fax: +33 (0) 134 81 03 59 Sales: pfg.cs.emea@meas-spec.com

ASIA

Measurement Specialties (China), Ltd. No. 26 Langshan Road Shenzhen High-Tech Park (North) Nanshan District, Shenzhen 518107 China Tel: +86 755 3330 5088 Fax: +86 755 3330 5099 Sales: pfg.cs.asia@meas-spec.com

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.