

L size	11.2 ±0.3mm
W size	10.0 ±0.3mm
T size	4.0 mm
Size code in inch (mm)	4440 (112100)

3.0

(Tolerance: ±0.3 in mm)

Rated current (Isat) is specified when the decrease of the initial

Rated current (Itemp) is specified when temperature of the inductor is

Packaging code	Specifications	Minimum quantity
=P3	$\phi$ 330mm Embossed taping	500

Mass (Typ.)	Mass (Typ.)	
1 piece	2.35g	

## Specifications

Inductance	3.3µH ±20%
Inductance test frequency	0.1MHz
Rated current (Isat) (Based on Inductance change)	9800mA
Rated current (Itemp) (Based on Temperature rise)	9000mA
Max. of DC resistance	0.0101Ω
Operating temperature range (Self-temperature rise is included)	-40 to 125°C
Class of magnetic shield	Metal Alloy
Absolute maximum voltage	30Vdc
Series	FDVE1040

### 🔔 Attention


1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

### Chart of characteristic data (The charts below may show another part number which shares its characteristics.)



2 of 2

#### 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata: FDVE1040-H-3R3M=P3