

	2		1									
	LOC DIST AG 00	P LTF	REVISIONS	DATE	DWN	APVD						
1	MATERIAL: HOUSING: GLASS-FILLED POLYES CONTACT: BERYLLIUM COPPER.	F2 STER		11MAR11	RK	HMR						
2	CONTACT PLATED WITH 0.00254 [.000100] TIN-LEAD OVER ALL.											
3	AREA OVER 0.00127 [.000050] NICKEL OVER ALL.											
4	CONTACT PLATED WITH 0.00076 [.000030] GOLD IN CONTACT AREA OVER 0.00127 [.000050] NICKEL OVER ALL.											
5	A PART NO. DENOTES INDIVIDUAL TWO POSITION SHUNT, WHICH IS PACKAGED ON BREAKAWAY COMBS OF TEN SHUNTS.											
6. A	5. CONNECTOR MATES WITH WIRE WRAP POSTS, 0.64 [.025] SQUARE OR ROUND AND 0.56 [.022] X 0.66 [.026] POSTS. LENGTH 5.08 [.200] MINIMUM. A CONTACT PLATED WITH 0.00254 [.000100] MATTE TIN OVER ALL.											
<u>^</u>												
9 PA	PRELIMINARY P/N - NOT RELEASED	P FOI	R PRODUCTION				g 531230					

		OBS	DLETE		8 5	531230-	-5 /9
					[	531230-	4 /5
				4	Ĺ	531230-	-3 5
				3	Ę	531230-	-2/5
				$\overline{2}$	Ľ	531230-	-1 5
				FINISH	F	PART NL	JMER
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 3-12-91 R.TALLEY снк –		E TE	TE	E Connectivi	ty
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		SHUNT		
	0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± 0.26 [.010]	PRODUCT SPEC 108-9057 APPLICATION SPEC	LOW PROFILE SHUNT CONNECTOR 5.08 [.200] CL -				
	3 PLC ± 0.26 [.010] 4 PLC ± - ANGLES ± -	114-1059	SIZE CAGE CO				RESTRICTED TO
	FINISH SEE TABLE	WEIGHT	<u>A2 0077</u>	79 <b>C-</b> 5312	230		—
		CUSTOMER DRAWING		SC,	ALE 4:1	SHEET 1 OF	$1 \int F^{\text{Rev}} F^2$

А

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 531230-3