

100mA - 150mA, 75V Surface Mount Switching Diode

FEATURES

- Low power loss, high efficiency
- High surge current capability
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant

APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- Lighting application
- On-board DC/DC converter

MECHANICAL DATA

- Molding compound meets UL 94HB flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1A whisker test
- Polarity: Indicated by cathode band

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	100, 150	mA
V_{RRM}	75	V
Configuration	Single die	



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)					
PARAMETER	SYMBOL	TS4148	TS4148	TS4148	UNIT
Package		0603 (Ceramics)	0805 (Ceramics)	1206 (Ceramics)	
Repetitive peak reverse voltage	V_{RRM}	75			V
Forward current	I_F	100	150	150	mA
Non-repetitive peak forward surge current	t = 1s	0.4	0.5		A
	t = 8.3ms	0.8	2.0		A
Junction temperature range	T_J	-55 to +150	-55 to +175	-55 to +150	$^\circ\text{C}$
Storage temperature range	T_{STG}	-55 to +150	-55 to +175	-55 to +150	$^\circ\text{C}$

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	TYP	UNIT
Junction-to-ambient thermal resistance	$R_{\theta JA}$	375	°C/W

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage ⁽¹⁾	0603, 1206 (Ceramics)	$I_F = 10\text{mA}, T_J = 25^\circ\text{C}$	V_F	-	1.00	V
	0805 (Ceramics)	$I_F = 100\text{mA}, T_J = 25^\circ\text{C}$		-	1.00	V
	0603, 1206 (Ceramics)	$I_F = 100\text{mA}, T_J = 25^\circ\text{C}$		-	1.25	V
Reverse current @ rated V_R ⁽²⁾		$V_R = 20\text{V}, T_J = 25^\circ\text{C}$	I_R	-	25	nA
		$V_R = 75\text{V}, T_J = 25^\circ\text{C}$		-	5	μA
Reverse recovery time		$I_F = 10\text{mA}, I_R = 10\text{mA}, R_L = 100\Omega$	t_{rr}	-	4	ns
Junction capacitance		1MHz, $V_R = 0\text{V}$	C_J	-	4	pF

Notes:

1. Pulse test with $PW = 0.3\text{ms}$
2. Pulse test with $PW = 30\text{ms}$

ORDERING INFORMATION		
ORDERING CODE	PACKAGE	PACKING
TS4148 RCG	0603 (Ceramics)	10,000 / 13" Tape & Reel
TS4148 RBG	0805 (Ceramics)	10,000 / 13" Tape & Reel
TS4148 RAG	1206 (Ceramics)	10,000 / 13" Tape & Reel

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Typical Reverse Characteristics




Fig.2 Typical Forward Characteristics




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Typical Reverse Characteristics





Fig.6 Typical Forward Characteristics



CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.7 Admissible Power Dissipation Curve




Fig.8 Typical Junction Capacitance




Fig.9 Typical Junction Capacitance







Fig.10 Typical Junction Capacitance




PACKAGE OUTLINE DIMENSIONS

0603 (Ceramics)



SUGGESTED PAD LAYOUT





NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. PACKAGE SIZE CODE REFERENCE:
EIA (inch) NAME: 0603 (0.063in x 0.031in)
IEC (metric) NAME: 1608 (1.6mm x 0.8mm)
3. DWG NO. REF: HQ2SD07-0603C-048 REV A.

PACKAGE OUTLINE DIMENSIONS

0805 (Ceramics)






SUGGESTED PAD LAYOUT

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. PACKAGE SIZE CODE REFERENCE:
EIA (inch) NAME: 0805 (0.079in x 0.049in)
IEC (metric) NAME: 2012 (2.0mm x1.25mm)
3. DWG NO. REF: HQ2SD07-0805-042 REV A.

PACKAGE OUTLINE DIMENSIONS

1206 (Ceramics)



NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. PACKAGE SIZE CODE REFERENCE:
EIA (inch) NAME: 1206 (0.126in x 0.063in)
IEC (metric) NAME: 3216 (3.2mm x 1.6mm)
3. DWG NO. REF: HQ2SD07-1206C-049 REV A.

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.