


# PG & Metric Metal Cable Glands



## SPECIFICATIONS

### Material:

- Nut: Lock Nut, Body: Brass, Nickel Plated
- Claw: Nylon 66, UL94V-2
- Washer, Seal: EPDM Rubber



### PG Thread (Type II)

Cable glands	A	Cable Range
PG7	12.8	3-6.5
PG9	15.5	4-8
PG11	19.0	6-10
PG13.5	20.8	6-12
PG16	23.0	10-13
PG21	28.8	14-18
PG29	37.5	20-25
PG36	47.5	22-32
PG42	54.5	32-38
PG48	59.8	37-44

### Metric Thread (Type II)

Cable glands	Pitch (mm)	A	Cable Range
M12	1.5	12.4	3-6
M16	1.5	16.4	5-9
M20	1.5	20.4	9-13
M25	1.5	25.4	11-16
M32	1.5	32.4	14-21
M40	1.5	40.5	19-27
M50	1.5	50.5	24-35
M63	1.5	63.5	38-48

## ORDER INFORMATION

**CG** - **PG** **7** **B** **S** **M** **0** **R**

1 2 3 4 5 6 7 8

1.SERIES NO.  
CG: Cable Glands

3.NO. OF CONTACTS  
(PG):7 9 11 13.5 16  
21 29 36 42 48  
(M):12 16 20 25 32 40  
50 63

5.INSULATOR COLOR  
S:Silver

7.PACKAGING  
0:Bulk

2.THREAD TYPE  
PG:PG Thread  
M:Metric Thread

4.CONNECTOR TYPE  
B:Type II (Split claw)

6.HOOD TYPE  
M:Metal

8.R:RoHS