

## MM54HCT373/MM74HCT373 TRI-STATE® Octal D-Type Latch MM54HCT374/MM74HCT374 TRI-STATE Octal D-Type Flip-Flop

### General Description

The MM54HCT373/MM74HCT373 octal D-type latches and MM54HCT374/MM74HCT374 Octal D-type flip flops advanced silicon-gate CMOS technology, which provides the inherent benefits of low power consumption and wide power supply range, but are LS-TTL input and output characteristic & pin-out compatible. The TRI-STATE outputs are capable of driving 15 LS-TTL loads. All inputs are protected from damage due to static discharge by internal diodes to V<sub>CC</sub> and ground.

When the MM54HCT373/MM74HCT373 LATCH ENABLE input is high, the Q outputs will follow the D inputs. When the LATCH ENABLE goes low, data at the D inputs will be retained at the outputs until LATCH ENABLE returns high again. When a high logic level is applied to the OUTPUT CONTROL input, all outputs go to a high impedance state, regardless of what signals are present at the other inputs and the state of the storage elements.

The MM54HCT374/MM74HCT374 are positive edge triggered flip-flops. Data at the D inputs, meeting the setup and hold time requirements, are transferred to the Q outputs on


positive going transitions of the CLOCK (CK) input. When a high logic level is applied to the OUTPUT CONTROL (OC) input, all outputs go to a high impedance state, regardless of what signals are present at the other inputs and the state of the storage elements.

MM54HCT/MM74HCT devices are intended to interface between TTL and NMOS components and standard CMOS devices. These parts are also plug in replacements for LS-TTL devices and can be used to reduce power consumption in existing designs.

### Features

- TTL input characteristic compatible
- Typical propagation delay: 20 ns
- Low input current: 1  $\mu$ A maximum
- Low quiescent current: 80  $\mu$ A maximum
- Compatible with bus-oriented systems
- Output drive capability: 15 LS-TTL loads

### Connection Diagram



**Top View**  
**'HC373**  
Order Number MM54HCT373 or MM74HCT373

**Top View**  
**'HC374**  
Order Number MM54HCT374 or MM74HCT374

TRI-STATE® is a registered trademark of National Semiconductor Corporation.

**Absolute Maximum Ratings** (Notes 1 & 2)  
**If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.**

Supply Voltage ( $V_{CC}$ )	−0.5 to +7.0V
DC Input Voltage ( $V_{IN}$ )	−1.5 to $V_{CC} + 1.5V$
DC Output Voltage ( $V_{OUT}$ )	−0.5 to $V_{CC} + 0.5V$
Clamp Diode Current ( $I_{IK}, I_{OK}$ )	±20 mA
DC Output Current, per pin ( $I_{OUT}$ )	±35 mA
DC $V_{CC}$ or GND Current, per pin ( $I_{CC}$ )	±70 mA
Storage Temperature Range ( $T_{STG}$ )	−65°C to +150°C
Power Dissipation ( $P_D$ ) (Note 3)	600 mW
S.O. Package only	500 mW
Lead Temp. ( $T_L$ ) (Soldering 10 seconds)	260°C

### Operating Conditions

	Min	Max	Units
Supply Voltage ( $V_{CC}$ )	4.5	5.5	V
DC Input or Output Voltage ( $V_{IN}, V_{OUT}$ )	0	$V_{CC}$	V
Operating Temp. Range ( $T_A$ )			
MM74HCT	−40	+85	°C
MM54HCT	−55	+125	°C
Input Rise or Fall Times ( $t_r, t_f$ )		500	ns

### DC Electrical Characteristics

$V_{CC} = 5V \pm 10\%$  (unless otherwise specified)

Symbol	Parameter	Conditions	$T_A = 25^\circ C$		<b>74HCT</b>	<b>54HCT</b>	Units
			Typ	Guaranteed Limits			
$V_{IH}$	Minimum High Level Input Voltage			2.0	2.0	2.0	V
$V_{IL}$	Maximum Low Level Input Voltage			0.8	0.8	0.8	V
$V_{OH}$	Minimum High Level Output Voltage	$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  = 20 \mu A$ $ I_{OUT}  = 6.0 \text{ mA}, V_{CC} = 4.5V$ $ I_{OUT}  = 7.2 \text{ mA}, V_{CC} = 5.5V$	$V_{CC}$ 4.2 5.7	$V_{CC} - 0.1$ 3.98 4.98	$V_{CC} - 0.1$ 3.84 4.84	$V_{CC} - 0.1$ 3.7 4.7	V V V
$V_{OL}$	Maximum Low Level Voltage	$V_{IN} = V_{IH}$ or $V_{IL}$ $ I_{OUT}  = 20 \mu A$ $ I_{OUT}  = 6.0 \text{ mA}, V_{CC} = 4.5V$ $ I_{OUT}  = 7.2 \text{ mA}, V_{CC} = 5.5V$	0 0.2 0.2	0.1 0.26 0.26	0.1 0.33 0.33	0.1 0.4 0.4	V V V
$I_{IN}$	Maximum Input Current	$V_{IN} = V_{CC}$ or GND, $V_{IH}$ or $V_{IL}$		±0.1	±1.0	±1.0	μA
$I_{OZ}$	Maximum TRI-STATE Output Leakage Current	$V_{OUT} = V_{CC}$ or GND Enable = $V_{IH}$ or $V_{IL}$		±0.5	±5.0	±10	μA
$I_{CC}$	Maximum Quiescent Supply Current	$V_{IN} = V_{CC}$ or GND $I_{OUT} = 0 \mu A$		8.0	80	160	μA
		$V_{IN} = 2.4V$ or $0.5V$ (Note 4)		1.0	1.3	1.5	mA

Note 1: Absolute Maximum Ratings are those values beyond which damage to the device may occur.

Note 2: Unless otherwise specified all voltages are referenced to ground.

Note 3: Power Dissipation temperature derating — plastic "N" package: −12 mW/°C from 65°C to 85°C; ceramic "J" package: −12 mW/°C from 100°C to 125°C.

Note 4: Measured per pin. All others tied to  $V_{CC}$  or ground.

## AC Electrical Characteristics MM54HCT373/MM74HCT373

$V_{CC} = 5.0V$ ,  $t_r = t_f = 6$  ns  $T_A = 25^\circ C$  (unless otherwise specified)

Symbol	Parameter	Conditions	Typ	Guaranteed Limit	Units
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Data to Output	$C_L = 45$ pF	18	25	ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Latch Enable to Output	$C_L = 45$ pF	21	30	ns
$t_{PZH}, t_{PZL}$	Maximum Enable Propagation Delay Control to Output	$C_L = 45$ pF $R_L = 1$ kΩ	20	28	ns
$t_{PHZ}, t_{PLZ}$	Maximum Disable Propagation Delay Control to Output	$C_L = 5$ pF $R_L = 1$ kΩ	18	25	ns
$t_W$	Minimum Clock Pulse Width			16	ns
$t_S$	Minimum Setup Time Data to Clock			5	ns
$t_H$	Minimum Hold Time Clock to Data			10	ns

## AC Electrical Characteristics MM54HCT373/MM74HCT373

$V_{CC} = 5.0V \pm 10\%$ ,  $t_r = t_f = 6$  ns (unless otherwise specified)

Symbol	Parameter	Conditions	$T_A = 25^\circ C$		$74HCT$	$54HCT$	Units
			Typ		$T_A = -40$ to $85^\circ C$	$T_A = -55$ to $125^\circ C$	
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Data to Output	$C_L = 50$ pF $C_L = 150$ pF	22 30	30 40	37 50	45 60	ns ns
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay Latch Enable to Output	$C_L = 50$ pF $C_L = 150$ pF	25 32	35 45	44 56	53 68	ns ns
$t_{PZH}, t_{PZL}$	Maximum Enable Propagation Delay Control to Output	$C_L = 50$ pF $C_L = 150$ pF $R_L = 1$ kΩ	21 30	30 40	37 50	45 60	ns ns
$t_{PHZ}, t_{PLZ}$	Maximum Disable Propagation Delay Control to Output	$C_L = 50$ pF $R_L = 1$ kΩ	21	30	37	45	ns
$t_{THL}, t_{TLH}$	Maximum Output Rise and Fall Time	$C_L = 50$ pF	8	12	15	18	ns
$t_W$	Minimum Clock Pulse Width			16	20	24	ns
$t_S$	Minimum Setup Time Data to Clock			5	6	8	ns
$t_H$	Minimum Hold Time Clock to Data			10	13	20	ns
$C_{IN}$	Maximum Input Capacitance			10	10	10	pF
$C_{OUT}$	Maximum Output Capacitance			20	20	20	pF
$C_{PD}$	Power Dissipation Capacitance (Note 5)	$OC = V_{CC}$ $OC = GND$		5 52			pF pF

Note 5:  $C_{PD}$  determines the no load dynamic power consumption,  $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$ , and the no load dynamic current consumption,  $I_S = C_{PD} V_{CC} f + I_{CC}$ .

## Truth Table

'373

Output Control	LE	Data	373 Output
L	H	H	H
L	H	L	L
L	L	X	$Q_0$
H	X	X	Z

H = high level, L = low level

$Q_0$  = level of output before steady-state input conditions were established.

Z = high impedance

'374

Output Control	Clock	Data	Output (374)
L	↑	H	H
L	↑	L	L
L	L	X	$Q_0$
H	X	X	Z

H = High Level, L = Low Level

X = Don't Care

↑ = Transition from low-to-high

Z = High impedance state

$Q_0$  = The level of the output before steady state input conditions were established.

## AC Electrical Characteristics MM54HCT374/MM74HCT374

$V_{CC} = 5.0V$ ,  $t_r = t_f = 6$  ns  $T_A = 25^\circ C$  (unless otherwise specified)

Symbol	Parameter	Conditions	Typ	Guaranteed Limit	Units
$f_{MAX}$	Maximum Clock Frequency		50	30	MHz
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay to Output	$C_L = 45$ pF	20	32	ns
$t_{PZH}, t_{PZL}$	Maximum Enable Propagation Delay Control to Output	$C_L = 45$ pF $R_L = 1$ kΩ	19	28	ns
$t_{PHZ}, t_{PLZ}$	Maximum Disable Propagation Delay Control to Output	$C_L = 5$ pF $R_L = 1$ kΩ	17	25	ns
$t_W$	Minimum Clock Pulse Width			20	ns
$t_S$	Minimum Setup Time Data to Clock			5	ns
$t_H$	Minimum Hold Time Clock to Data			16	ns



## AC Electrical Characteristics MM54HCT374/MM74HCT374

$V_{CC} = 5.0V \pm 10\%$ ,  $t_r = t_f = 6$  ns (unless otherwise specified)

Symbol	Parameter	Conditions	$T_A = 25^\circ C$		$74HCT$	$54HCT$	Units
			Typ		$T_A = -40$ to $85^\circ C$	$T_A = -55$ to $125^\circ C$	
$f_{MAX}$	Maximum Clock Frequency			30	24	20	MHz
$t_{PHL}, t_{PLH}$	Maximum Propagation Delay to Output	$C_L = 50$ pF $C_L = 150$ pF	22 30	36 46	45 57	48 69	ns ns
$t_{PZH}, t_{PZL}$	Maximum Enable Propagation Delay Control to Output	$C_L = 50$ pF $C_L = 150$ pF $R_L = 1$ kΩ	21 30	30 40	37 50	45 60	ns ns
$t_{PHZ}, t_{PLZ}$	Maximum Disable Propagation Delay Control to Output	$C_L = 50$ pF $R_L = 1$ kΩ	21	30	37	45	ns
$t_{THL}, t_{TLH}$	Maximum Output Rise and Fall Time	$C_L = 50$ pF	8	12	15	18	ns
$t_W$	Minimum Clock Pulse Width			16	20	24	ns
$t_S$	Minimum Setup Time Data to Clock			20	25	30	ns
$t_H$	Minimum Hold Time Clock to Data			5	5	5	ns
$C_{IN}$	Maximum Input Capacitance			10	10	10	pF
$C_{OUT}$	Maximum Output Capacitance			20	20	20	pF
$C_{PD}$	Power Dissipation Capacitance (Note 5)	$OC = V_{CC}$ $OC = GND$		5 58			pF pF


Note 5:  $C_{PD}$  determines the no load power consumption,  $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$ , and the no load dynamic current consumption,  $I_S = C_{PD} V_{CC} f + I_{CC}$ .

## Logic Diagrams




**MM54HCT373/MM74HCT373 TRI-STATE Octal D-Type Latch  
MM54HCT374/MM74HCT374 TRI-STATE Octal D-Type Flip-Flop**

**Physical Dimensions** inches (millimeters)



**Order Number MM54HCT373J, MM54HCT374J, MM74HCT373J, or MM74HCT374J  
NS Package Number J20A**



**Order Number MM74HCT373N or MM74HCT374N  
NS Package Number N20A**

**LIFE SUPPORT POLICY**

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

 National Semiconductor Corporation 1111 West Bardin Road Arlington, TX 76017 Tel: (800) 272-9959 Fax: (800) 737-7018	National Semiconductor Europe Fax: (+49) 0-180-530 85 86 Email: cnjwge@tevm2.nsc.com Deutsch Tel: (+49) 0-180-530 85 85 English Tel: (+49) 0-180-532 78 32 Francais Tel: (+49) 0-180-532 93 58 Italiano Tel: (+49) 0-180-534 16 80	National Semiconductor Hong Kong Ltd. 13th Floor, Straight Block, Ocean Centre, 5 Canton Rd. Tsimshatsui, Kowloon Hong Kong Tel: (852) 2736-1700 Fax: (852) 2736-9960	National Semiconductor Japan Ltd. Tel: 81-043-299-2309 Fax: 81-043-299-2408
--	--	---	---

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.